



PV243

# Clustering & Scalability

## LAB SESSION

Radoslav Husár

Software Engineer  
Red Hat

April 13, 2015

# Agenda

4 demos

- Building JGroups chat demo
- Building HA WebApp
  - Verifying failover

Homework

- Remote EJB load-balancing
- Clustered Remote Stateful Session Bean demo



# Priming Build

```
$ git clone https://github.com/qa/pv243-  
2015-clustering-seminar.git  
  
$ git checkout clustering-00  
  
$ cd chat-jgroups  
  
$ mvn clean install
```





# Chat over JGroups

# Chat

- Task

Finish implementation of a simple chat using JGroups API using default UDP stack. Notify when new member joins a chat “room” and display messages from all member. Send messages to all members. You can add bonus features but keep the message format the same.

- Checkout `clustering-00` tag to start working



# Demo

```
$ cd chat-jgroups
$ mvn clean install
$ sudo ip route add 224.0.0.0/4 dev lo table
local
$ java -Duser.name="Radoslav Husar"
-Djava.net.preferIPv4Stack=true -classpath
target/chat-
jgroups.jar:target/dependency/jgroups-
3.4.3.Final.jar
cz.muni.fi.pv243.seminar.clustering/Chat -b
127.0.0.1
```





# Highly-Available WebApp

# WebApp

- Task:

Implement missing pieces in the WebApp to make it highly-available. Let the simple Servlet return number of times the Servlet has been invoked so that in case of failover it will enable us to verify if the session state is as expected. Add `?readonly=true` and `?invalidate=true` options.

- Checkout `clustering-01` tag to start working





# Deploy the App

- Build + copy to standalone/deployments
- `./standalone.sh -c standalone-ha.xml`
- `./standalone.sh -c standalone-ha.xml \`  
`-Djboss.socket.binding.port-offset=100 \`  
`-Djboss.node.name=node2`
- Why use port-offset?
- How to simulate failover?





# Load-balancing Remote Stateless Session Beans and Remote Cluster-Aware Stateful Session Beans

# Clustered beans

- Task  
Implement clustered Stateless Session Bean and clustered Stateful Session Bean. Implement a remote EJB clients which connects to WildFly cluster and invokes operations on the beans. Demonstrate the load-balancing of SLSB and SFSB failover.
- Checkout `clustering-02` tag to start working



# Steps to run the app (1)

- Deploy jar containing the beans to all servers in the cluster
- Start servers  
You need to name servers differently and run one with a port offset.
  - `./bin/standalone.sh -c standalone-ha.xml -Djboss.node.name=node1`
  - `./bin/standalone.sh -c standalone-ha.xml -Djboss.node.name=node2 -Djboss.socket.binding.port-offset=100`



## Steps to run the app (2)

- Run the remote client
  - You need to have on classpath:
    - `$JBOSS_HOME/bin/client/jboss-client.jar`
    - interface of the bean which you'll call remotely
  - `cd client-side`
  - `mvn exec:java`  
`-Dexec.mainClass=cz.muni.fi.pv243.seminar.clustering.ejb.remote.client.StatelessRemoteClient`
  - `mvn exec:java`  
`-Dexec.mainClass=cz.muni.fi.pv243.seminar.clustering.ejb.remote.client.StatefulRemoteClient`

